



ETX-200VMDM

Volume and Multi-dimensional Measurement Reader

Overhead Static Dimensioning System

Scantech-ID's VM200 is a compact and robust handheld multi-dimensional measuring device, its intuitive reading, unmatched fact performance and optimal price make it the best choice in the market.

VM200 is a easily carry device, with its intelligent reading zone detection and smart guiding aimer will alarm continuous beeps with flashing red LED when no object is detected inside the good reading zone which leads customers to measure very intuitively and quickly. Furthermore, with its configurable buttons allow the operation flow best fit the application that enables customers to optimize various multi-dimensional measurement applications, quickly and effectively.

Whether it is a courier and express delivery company, a post office, a shipping station, a retail ship-from-store location, an airport check-in counter, an inbound station of a warehouse, the VM200 system provides an efficient way to achieve quick measuring and space optimization. The VM200 system instantly and accurately measure the dimensions of an object. This optimally priced dimensioning device provides quick return on investment for applications where the previous alternative was a tape or a ruler measure. Manual tape measurements resulted in lower accuracy, inconsistency and reduced productivity. VM200 built in both 2D barcode and 3D measurement readers, make it a compact device to support multiple functions application and save customer's deployment space.

The VM200 device increases accuracy, consistency and user productivity in various applications - increasing revenue capture, reducing shipping chargebacks and throughput bottlenecks, and optimizing storage space, workflow and load planning.

VM200 is a must-have and best choice for companies looking to measure packages, cartons, and objects to optimize its workload, workflow and space.



Features

- Easily handheld and carry
- Measure cuboidal and irregular shapes.
- No extra ruler and no self pre-calibration needed.
- Intuitive reading and unmatched fact performance.
- 3D volume measurement and 2D Barcode reader.
- Data output : W-H-L and sum dimension values, volume and dimensional weight or barcode data.
- Measurement time: less than 1 second.
- 2 buttons and 6 optional function to well fit your app.


- Min. 10cm cube, Max. 80cm cube.
- Accuracy: d=2, less than 12cm deviation.
- Ambient lighting: 0 to 3000 Lux., avoid direct sunlight.
- Communication interface: USB or RS-232.
- Tools and command protocol.

Package color:


All opaque packaging except black, very glossy and transparent.

Smart "+" guiding aimer

Intelligent reading zone detection and smart guiding aimer leads the measuring quickly.



Reading angle



Specifications

Physical Characteristics

VM200 (WxLxH)	W11.5 x H7 x L18 cm (W3.45 x H2.1 x L5.4 inches)
Weight (g/oz)	280 g (9.88 oz)

Electrical Characteristics

Input voltage	DC 5V
Power consumption	Standby 225mA, Operating 465mA
Host System Interface	USB or RS-232 wired cable

Aimer Specifications

Wavelength	650±10nm Red VLD IEC
Classification	60825-1:2014 Class 1

Environmental Specifications

Operating temperature	0°C to 40°C (32°F to 104°F)
Storage temperature	-20°C to 60°C (-4°F to 140°F)
Relative humidity	0 to 70% relative humidity, non condensing
Ambient light	0 to 3000 lux, avoid direct sunlight
Sealing protection	IP54

Performance Specifications

Field of view	Horizontal 52°, Vertical 30°
Shape	Cuboidal and irregular shapes
Accuracy	d=2, less than ±2cm deviation
Measurement time	Less than 1 second
Object size	10 cm / 0.394 inches cube (OIML 20cm cube)
Min. cube	80 cm / 31.5 inches cube (OIML 60cm cube)
Max. cube	All opaque packaging except black, very glossy and transparent
Color	glossy and transparent
Measurement angle	Pitch: 35° ~ 65°, Skew: ± 15°
Measurement surface	No black, transparent or very shining background
Indicator	Beep and LED (Green, Red and Orange)
Certification	CE, FCC, LVD, OIML/MID certification, apply NTEP certificate

Tools and SDK

Configuration tool	VMSet
Data viewer tool	VMView
SDK	Communication command protocol