



ETX-330RPR

High-End Pos Printer

Specifications

General	
Printing method	Direct thermal
Printing speed	300mm/s
Paper width	82.5 mm 80mm/58mm
Print width	72 mm (adjustable by commands)
Maximun paper diameter	83mm
Paper thickness	0.06-0.08mm
Column capacity	576 dots/line 512/line (adjustable by commands)
Line space	3.75mm (Changeable by commands)
Commands	Compatible with ESC/POS
Interface type	USB + Lan/USB + Serial/USB + Serial + WIFI (Option)/USB + serial + Bluetooth(option)
Character size	ANK, Font A: 12 * 24dots Font B: 9 * 17 dots Simplified / traditional Chinese: 24*24 dots
Dimension	133 * 126 * 130mm (D * W * H)
Gross weight	1.2kg
Bar code	UPC-A/ UPC-E/ JAN(EAN13) / JAN8 (EAN8) / CODE39/ ITF/ CODABAR/ CODE93/ CODE128
2-dimension code	QR CODE / PDF417
Code page	PC347 (Standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), WesEuropeGreek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), PC858, Iranll, Latvian, Arabic, PT151 (L251
Cutter	Partial
Cutter life	2 million cuts



Features

- Compact design printer, modern appearance, convenient printing and high printing speed.
- 58mm/ 80mm/ 82.5mm paper width available.
- IAP function supports firmware update within 5S. Make printer maintained easily.
- Reliable cutter with intelligent code to prevent cutter from cutter jammed.
- Metallic frame mechanism.
- Supports Win XP/ Win Vista/ Win 7/ Win 8/ Win 8.1/ Win 10/ Linux)

Print head life	150 KM
Input buffer	2048 Kbytes
NV Flash	256 Kbytes
Power adaptor	AC110V/220V,50-60Hz
Power source	DC 24V/2.5A
Cash drawer output	DC 24V/1A
Work environment	Temperature: 0~45°C, humidity: 10~80RH%
Storage environment	Temperature: -10~60°C, humidity: 10~90RH%

