



ETX-337X2POS

7" POS Display



Features

- Sealed zero-bezel design with tamper proof glass
- Optional VESA mounting holes at the bottom, can fit to medical carts easily
- Step edge design on the back cover, allow easy mounting to any equipment or furniture.
- SVGA (800 x 480) resolution
- USB interface, powered by USB interface
- Available with two stands: Standard Stand and Long Pole Stand

Specifications

System

Processor	Intel® Tiger Lake i3-1115G4
Memory	4GB DDR4
Storage	128GB SSD (M.2)

Display

Size and Resolution	15.6" (1920 x 1080)
Touch Screen	True-Flat PCAP multi-touch

Expansion

M.2 (E Key)	1
-------------	---

I/O Ports

USB Type-A	4x USB3.0, 2x USB2.0, 1x USB2.0 (Front)
USB Type-C	1x USB3.0 (DP/ PD 5V/3A, 12V/3A, 19/5A)
Serial Port	3x RJ45
LAN	1x RJ45
Cash Drawer	1x RJ11
DC Jack	1x 4PIN (with latch)
Power Button	1

Optional I/O

Powered USB	1x Powered USB 12V, 1x Powered USB 24V
USB Type-A	2x USB2.0

Audio

Internal Speaker	1x 3W
------------------	-------

Indicator

Power Button w/ LED	1
---------------------	---

Power

Power Adapter	65W/19V (120W/19V with PUSB 12V & 24V)
---------------	--

Communication

WLAN + BT	802.11 series + BT5.2 (Option)
-----------	--------------------------------

Peripheral (option)

Camera	Front Camera (USB)
MSR	3-Track MSR (USB)
Fingerprint	Fingerprint Reader (USB)
iButton	iButton (USB)
Customer Display	LCM display 2 x 20 characters (USB)
2nd Display	11.6" 2nd Display

Certificate

EMC & Safety	FCC Class A, CE Mark, LVD
--------------	---------------------------

Environment

Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)
Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Humidity	20% ~ 85% RH non-condensing

Dimensions

W x D x H	368 x 233 x 265 mm
-----------	--------------------

Mounting

VESA Mount	100 x 100 mm
------------	--------------

OS Supported

Windows 10 IoT Enterprise, Linux, Android 13.0