

## Label Printing Scale bPlus



### Features

- Fast weighing, serving and labeling compliant with today's regulations.
- Proven, mature software extended with next-generation functionalities.
- Compatibility with predecessors, makes it easy for employees who know METTLER TOLEDO legacy scales to work with the new scale.
- Smart software solutions allow to run bPlus and predecessor scales in one store.
- Professional PC-software for integration with ERP system.
- Smart management for optimal data integrity and operational uptime of the scales.

## Specifications

### Operator Display \*

|            |  |
|------------|--|
| Weight     | 6 digits                                     |
| Tare       | 5 digits                                     |
| Price / Kg | 6 digits                                     |
| Total      | 7 digits                                     |
| Text Line  | 16 alphanumeric characters (dot matrix line) |

### Customer Display \*

|            |  |
|------------|--|
| Weight     | 6 digits                                     |
| Tare       | 5 digits                                     |
| Price / Kg | 6 digits                                     |
| Total      | 7 digits                                     |
| Text Line  | 16 alphanumeric characters (dot matrix line) |

### Housing

- Dark grey
- Die-cast aluminium housing
- Stainless steel platter
- Adjustable feet

### Keyboard

- Easy to clean membrane keyboard
- 98 membrane keys with pressure point
- 70 preset keys with two layers for assigning 140 PLUs
- Separate individually configurable function keys

### Printer

- Thermal printer for receipts, labels and linerless \*\*
- Printing speed up to 125 mm/s
- Print resolution 8 dots/mm
- Roll width labels 65 mm
- and linerless
- Printable width 56 mm
- Roll diameter max. 120 mm

### Interfaces

- 2 RS232 serial interfaces
- 1 RJ45 Ethernet interface
- 2 USB interfaces
- 1 RJ11 interface (12 V) for controlling the cash register

### Networking and Data Transfer

- 10/100 Base T Ethernet, TCP/IP, USB, DHCP, Wireless LAN \*\*
- DHCP support for automated network setup
- Hub less network connection
- Automatic backup
- Smart management functions for transmitting and securing production and configuration data via USB stick

### Technical Data

|                  |                        |         |          |
|------------------|------------------------|---------|----------|
| Weighing Range   | 3/6 kg                 | 6/15 kg | 15/30 kg |
| Graduation       | 1/2 g                  | 2/5 g   | 5/10 g   |
| Minimum capacity | 40 g                   | 100 g   | 100 g    |
|                  | Automatic zero-setting |         |          |

### Electrical Characteristics

|                           |                        |
|---------------------------|------------------------|
| Power Consumption         | 100-240 V AC, 50/60 Hz |
| Standby power consumption | < 0,5 W                |
| Working power efficiency  | > 85 percent           |

### Accessories and Options

- Power cord
- Wireless kit for Wireless data transmission according to IEEE802.11b/g/n standard
- Linerless printer

\* Different availability of display types depending on region: Segment LCD display with orange backlight; 1line dot Matrix display with orange or white backlight.

\*\* optional